MITSUBISHI	mobile XGA Data Projector ver1.0 EX53U
Display Technology	0.55" 1-Chip DMD, 12deg.LVDS, DDP2230
Resolution	1024 x 768 (Total 786,432 pixels)
Brightness	Marketing Spec: 3000lm (Normal Mode), 2250 lm (Low Mode), Min: 2400 lm (Normal Mod
Color Wheel	6seg. Color Wheel (R/G/B/W/Y/C)
Contrast Ratio	2000 : 1 (on/off)
Zoom/Focus	Manual Focus & Zoom Lens(Zoom Ratio 1.2:1)
Projection Lens	f=18.4 ~22.0 mm, F=2.5-2.8, (3.3-4.0m@100")
Off set axis	14.3:-1
Picture Size	40 -300(Wide) inch
Source Lamp	Normal Mode: 280W (Shut Off Time: 2000hrs), Low Mode:230W (Shut Off Time: 3000hrs)
PC Compatibility	Resolution ; 640 x480(Expand) - 1024 x 768(Real) - 1280 x 1024 (Compressed), include WXGA Sync on Green available
Video Compatibility	NTSC / NTSC 4.43 / PAL (including PAL-M, N) / SECAM / PAL-60 Component Video ; 480i/p(525i/p), 576i/p(625i/p), 720p(750p), 1080i(1125i 60Hz), 1080i(1125i 50Hz), (1080i(1250i 50Hz) is not available)
Input Terminals	RGB ; mini D-sub 15pin x 2, DVI-D PC Audio ; Stereo mini jack (φ3.5mm) x 1 Video ; RCA x 1 + S-VIDEO x 1 Video Audio ; RCA jack (L/R) x 1
Output Terminal	RGB ; mini D-sub 15pin x 1 Audio ; Stereo mini jack (φ3.5mm) x 1
Communication Terminal	USB terminal for Page Up/Down RS232C; D-sub 9pin x 1
Scanning Rate	[H] 15 - 80 kHz [V] 50 - 85 Hz [Dot clock] max.110 MHz
Audio Speaker	2 W Mono
Height Adjuster	Front Lifting leg×1/Rearward lifting leg×
Outstanding Feature	● Lens-center desigr ● Top Access Lamp ● Color Enhancer2 (BrilliantColorTM+Dynamic lamp power contrc ● Wall Screen (Beige/Blue/Green/Pink/Black Board/Whiteboarc ● Metal bar for security loch ● User programmable Splash screen (Screen capture ● Password Lock (Display Input/Menu Access/Splash ID Screer ● Instant Shutdowr ● Aspect 16:9 Position (center/upper/lowe ● Digital Keystone Correction (V only (MAX +15/-15deg （+/- 20 steps)) ● Video Line Doubler ; 2:3 / 2:2 pull-dow ● 12 Language OSD ● Wireless image transmittance from PC (Windows 2000/XF
Hand Remote unit	(1) Projector Fully Control (2) Power Point Page Up/Down via USB
Power consumption	390W (3.9A)
Dimension	332 x 102 x 250mm (W xHx D) , Not included protrusior
Weight	3.4kg(7.5lbs) (TBD)
Power requirements	AC 100 - 240 V, 50/60Hz
Fan Noise	39 dBA (Low Mode 34dBA)、Sea-level (TBD)
Package Dimension	400 x 314 x 243mm (W xHx D)
Package Weight	5.2kg (TBD)
Supplied Accessories	Soft carrying bag x1 Remote control x1(With 2 batteries) Power cable(1.8m) x1 VGA(D-sub) cable(1.8m) x1 User-Manual x1(CD-ROM) Safety manual x1(with Safety Manual and Quick Start Gudie) Lens Cap
Wireless function	IEEE 802.11b/g RJ45 terminal for set-up External Antenna
Optional Accessories	Option Lamp (VLT-XD520LP)