

M283X, M323X, M363X, M403X, M323W, M363W and M403H digital projectors

NEC M Series

Easy to use and at the right price, M Series projectors provide all the essential features that you need for brilliant display in classrooms and meeting rooms while providing low cost of ownership with minimal maintenance.



Essential Features for Educational Facilities

- Plug and Play intuitive setup and operation
- Bright images easily viewed in any application
- Versatile, color-coded connections to computer, video sources and external monitor
- Automatic keystone correction technology instantly projects a square image even when the projector is set up at a steep offset angle to the screen
- AutoSense™ intuitively syncs the projector with most computer signals and features one-touch image optimization
- One-touch source changes and complete menu control using the intuitive projector keypad
- Powerful 20-watt speaker provides volume needed for large rooms
- High contrast images (10,000:1) from the latest Texas Instruments DLP engine featuring BrilliantColor™ technology with improved color accuracy
- With XGA, WXGA and 1080p native resolutions, high brightness up to 4000 lumens and patented NEC technologies, M Series projectors display impressive image quality

Designed with the Environment in Mind

- Extended lamp life with ECO Mode™ technology increases lamp life up to 10,000 hours, while lowering power consumption
- Power management enables projector to automatically turn off when an incoming signal is not detected from any of the inputs
- Auto Power On via the RGB (15-pin) input connector when a signal is detected from a computer
- Carbon savings meter calculates the positive effects of operating the projector in ECO Mode, which is encouraged by an optional message at startup. A green ECO Mode button on the remote control makes the switch easy.
- Quick start (3 to 4 seconds) lets you begin presenting in seconds
- Sleep timer can be set to automatically turn off the projector at set countdown times
- Low power consumption (0.2W in stand-by mode) minimizes energy costs


High Performance Portable Projectors

Advanced Networking Capabilities

- Integrated RJ45 connection for quick connection to the LAN (10/100 base-T capability)
- Remote diagnostics enable the user to monitor and make adjustments to the projector remotely
- PC CTL 4.0 controls the power switching input selection and other functions while managing lamp usage and a variety of other vital information over the network. Email notification and projector scheduling for better asset management is included with the software.
- PC CTL 5.0 for MAC users
- Control and receive important broadcast messages via Crestron Roomview™
- Wireless Image Utility (WIU) sends images directly from an iPad to the projector (requires wireless LAN module NP02LM1)
- Simple Access Point Sending photos and documents have never been easier from a computer or iPad.
- MultiPresenter enables up to 16 wireless devices to be connected to the projector simultaneously with access controlled by the moderator.

Image Express Lite

Dedicated projector software provides wired and wireless data and audio transmission via peer-to-peer or over the network.



Advanced ECO Mode

ECO Mode


Lamp control selections with the ability to change power dependent on the ambient lighting conditions. With a built-in ambient light sensor, automatic adjustment of the projector's lamp provides unprecedented brightness control resulting in bright images for most environments. Automatically dim the image with the new Auto-dim feature to control the brightness of static images and extend lamp life. Constant brightness control prevents the usual drop in brightness over time while maximizing lamp life.

Built-in wall color correction presets

These provide for adaptive color tone correction to display properly on non-white surfaces.



On a green wall...



BEFORE auto wall correction



AFTER auto wall correction

M Series Features

Top cover lamp change

This feature provides for easy lamp changes without removal of the projector from the mount.



Active lens cover

This cover enables presenters to immediately mute the audio and video, then seconds later lower the lamp brightness to 25% for a short period of time.



Get Connected with a Wide Selection of Inputs

- Dual HDMI inputs (one MHL compatible) ensure quick switching between presentations
- Four audio inputs (mini-stereo, R/L RCA and 2 HDMI™) make it easy to add sound to enhance your presentations

Remote control

Easy control from remote allows you to adjust lamp mode, aspect ratio, volume and image all with the touch of a button.



Dual HDMI inputs

Among the M Series' wide selection of inputs are 2 HDMI w/HDCP for connecting to high-definition sources such as Blu-ray players, cable boxes, satellite receivers and personal computers.



Variable audio-out

This input enables the remote control to be used to adjust volume of self-powered external speakers that are connected to the projector. In stand-by mode, the audio-out stays active, allowing the last input used to pass to the self-powered external speakers.



Full HD 3D video (144Hz)

HDMI 3D can be viewed with 3rd party DLP-Link glasses or RF glasses paired with an RF emitter from Xpand or Volfoni. 3D computer images can be viewed using NEC active shutter glasses (NP02GL). 3D Ready M-Series Projectors use DLP Link™ technology, developed by Texas Instruments. M-Series projectors are certified as a display device for NVIDIA® 3D Vision™, which allows you to view 3D images using supported graphics boards or



USB Viewer

In instances when you'd prefer to leave your laptop behind for a presentation, M Series projectors can deliver a solution. Using the presentation conversion software included with your projector, simply place your file onto a USB drive and plug it into the projector's USB port. This allows you to display images stored as .jpgs from optional USB memory.



USB input

Your connection options go even further with the M Series. Connect your laptop or PC directly to the projector using the USB port and a standard USB cable.



			NP-M403H	NP-M323W / M363W	NP-M283X / M323X / M363X / M403X
Projection System			Single DLP® (0.65")	Single DLP® (0.65")	Single DLP® (0.55")
Resolution			1920 x 1080 (1080p Full HD)	1280 x 800 (WXGA)	1024 x 768 (XGA)
Lens			Manual zoom (x1.7) / manual focus, F=2.4 - 3.1, f=17.09 - 29.05mm, throw ratio 1.5 - 2.55	Manual zoom (x1.7) / manual focus, F=2.4 - 3.1, f=17.09 - 29.05mm, throw ratio 1.2 - 2.04	Manual zoom (x1.7) / manual focus, F=2.4 - 3.2, f=18.0 - 30.6mm, throw ratio 1.2 - 2.04
Light source (lamp)	ECO mode		162W	135W / 150W	120W / 135W / 150W / 162W
	ECO mode off		270W	225W / 250W	200W / 225W / 250W / 270W
Lamp life	ECO mode		8,000 H	8,000 H	10,000 / 8,000 / 8,000 / 8,000 H
	ECO mode off		3,500 H	3,500 H	4,500 / 3,500 / 3,500 / 3,500 H
Image size			30 to 300 inches	30 to 300 inches	30 to 300 inches
Light output	Normal		4,000 ANSI lumens	3,200 / 3,600 ANSI lumens	2,800 / 3,200 / 3,600 / 4,000 ANSI lumens
	ECO mode		Approximately 80% of normal		
Contrast ratio (white/black)			10,000:1		
Maximum resolution			Up to WUXGA (1920 x 1200)		
Synchronization range	Horizontal		15kHz to 100kHz (RGB: 24 kHz or over)		
	Vertical		50Hz to 120Hz (HDMI: 50 - 85Hz)		
Keystone correction	Horizontal		Manual: +/- 25 degrees		
	Vertical		Auto / manual: +/- 30 degrees		
Input terminals	Computer	Audio	Mini D-sub 15 pin x 1		
			Stereo mini jack x 1		
	Video	Audio	RCA x 1		
			(L/R) RCA x 1		
	HDMI		HDMI x 2 (HDMI 1 supports MHL function)		
	Microphone		Stereo mini jack, dynamic mic, condenser mic		
	3D Sync		Mini 3-pin		
	USB Port	Type A	USB 2.0 (USB viewer) powered		
Type B		USB display / mouse control			
Output terminals			Mini D-sub 15 pin x 1		
	Audio		Stereo mini jack x 1 (VAO)		
Wired LAN port			RJ45 (10 BASE-T / 100 BASE-TX) x 1		
Control terminals			D-Sub 9-pin x 1		
Built-in speaker			20W monaural		
Usage environment	Operational temperature		41 to 104 degrees Fahrenheit, 20 to 80% humidity (no condensation)		
	Storage temperature		14 to 122 degrees Fahrenheit, 20 to 80% humidity (no condensation)		
Power requirements			100-240 VAC 50/60Hz		
Input current			3.9 A to 1.9 A	3.6 A to 1.4 A	3.9 A to 1.5 A
Power consumption	ECO mode off		338W	283W / 316W	255W / 283W / 316W / 338W
	ECO mode		221W	186W/205W	170W/186W/205W/221W
	Standby (network)		0.5W or less		
	Standby (normal)		0.15W or less		
Net dimensions (W x H x D)			368 x 108 x 292mm (14.5" x 4.3" x 11.5")		
Weight			3.5kg / 7.7lbs		
Gross dimensions (W x D x H)			459 x 225 x 381mm (18.1" x 8.9" x 15.2")		
Gross weight			5.2kg / 11.5lbs		

UNIQUE FEATURES

BrilliantColor advanced video processing from Texas Instruments delivers more vibrant and realistic colors and blacks rich in detail.

DICOM Simulation enables users in medical training environments to display accurate diagnostic images

Advanced AccuBlend™ ensures detailed images when non-native resolution sources are connected to the projector

Filter Free with shielded engine eliminates the hassle and time spent monitoring and /or changing filters.

Built-in closed captioning enables decoding and display of text information from a video

64-step image magnification with location control

Countdown sleep timer can be set to automatically turn off the projector

WARRANTY

Registered owners receive a 2-year parts and labor warranty including InstaCare. The lamp is covered for one year or 500 hours, whichever comes first. InstaCare provides the original owner one year of either limited 3 business day repair/return or next business day exchange.

SHIPS WITH

Carrying case, remote control, batteries, power cord, RGB signal cable, built-in lens cover, user's manual on CD-ROM, quick start guide, and product registration card

ORDERING MODEL NUMBERS

NP-M283X
NP-M323X
NP-M363X
NP-M403X
NP-M323W
NP-M363W
NP-M403H

Accessories

NP01MR	IR receiver enables PJ remote to control PC and MAC functions
NP02LM1	802.11b/g/n wireless LAN adapter
SPKR30	Amplified 30-watt speaker
MP300CM	Ceiling mount
NP01UCM	Universal ceiling mount for projectors weighing less than 40 pounds
NP02GL	Active shutter 3D glasses (PC only)
SCP200	Adjustable suspended ceiling plate for use with ceiling mount
NP27LP	Replaceable lamp for M283X
NP28LP	Replacement lamp for M323X and M323W
NP29LP	Replacement lamp for M363X and M363W
NP30LP	Replacement lamp for M403X
RMT-PJ36	Replacement remote control
PWRCRD-PJPX	Power cable

Additional accessories are available, including screens, carts, mount accessories and replacement cables. Visit www.necdisplay.com for details.



Advanced AccuBlend, ECO Mode and Virtual Remote are trademarks of NEC Display Solutions. HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC. All other brand or product names are trademarks or registered trademarks of their respective holders. Product specifications subject to change.