## Nec M403W























**Brief Introduction** 

The standard portable Nec M403W 3D DLP projector has 4000 Ansi lumens, a contrast of 10000:1 and a WXGA 1280 x 800 resolution. The built-in ambient light sensor detects the ambient light in the room and automatically optimizes the image. The integrated media player allows files to be played directly. The horizontal and vertical keystone correction provides room for maneuver when setting up. As the M403W is equipped with a microphone jack plug and 20W loudspeaker, no additional audio system is required for presentations or training courses. 643 cm picture width, the projector will be able to illuminate well. The projector can manage rooms with residual light with a smaller image width, we would recommend a maximum of 429 cm here. Video signals 1080P and 3D are also no problem for the projector. The projector was launched in 2015 and is no longer sold by the manufacturer. 1 x 0,65" DLP Chip

Display Type

WXGA 16/10 Ti Digital Light Processing Chip

Ansi-Lumen Contrast Black Level Offset

4000 10000:1 full on/off 0,4000 min. Lumen

ω1600 Lux (bei 200 cm Screen)

0 10000:1 full on/off
0 0,16 min. Lumen

Resolution

Video Modes

Application

Light Source

Light Life

WXGA 1280 x 800 1.024.000 Pixel

WUXGA 1920 x 1200 compressed

Pal, SECAM, NTSC, HDTV 720p, 1080i, 1080p, 3D, EDTV 480p, 576p

Media player formats: JPEG

Frame-Packing (Full HD 3D) | Side-by-Side | Top-and-Bottom 3D Compatibility

Frame Sequential (3D Ready)

Standard-Portabel | External training and company presentations, as well as product

presentations.

Wide screen width or rooms with plenty of light (over 200 lumens).

270 / 162W im Eco Mode Lamp Articel Nr.: NP30LP / 100013543 3500 h. 8000 in Eco Mode

**Operating Costs** 14,29% / 0,06 €

Manual **Focus** 

Zoom Manual 1,67

F=2,4-3,1 f=17,09-29,05 mm Objective

Throw Ratio 1,22-2,07:1

Audio 20W Mono

Connections 2 x HDMI in


> D-sub 15pin in und out Cinch Video in

Cinch Stereo in S-Video in

Mini Jack Audio in und out

USB Typ A,B in RS232C Din 9 pin in

RJ45 in Mikrofon in





Ceiling Mounting

Power

Yes

320 / 210W in Eco Mode

Size WxHxD 368 x 108 x 291 mm (14,5"x4,3"x11,5") 11,57 L/dm<sup>3</sup>

Operating Noise 36 / 30 dB in Eco Mode

Weight 3,50 kg / 6,61 lbs.

Keystone Vert.: +/-30° automatisch

Hori.: +/-25°

Illumination -

Foot-Lamberts

**Features** 

Frequenz H-sync: 15-100 kHz V-sync: 50-120 Hz

149 fL / max. 643 cm screen width

511 cd/m<sup>2</sup>

Real Full HD 3D

■ Full HD 1080P compatible
■ Integrated Mediaplayer

■ Freeze

■ User logo

Eco Mode

Automatic and manual vertical keystone correction

Kensington Slot

■ Password protection

■ PJLink™

Optional Wi-Fi network compatible.

Lan network compatible.

Crestron®-Software compatible.

Ambient Light Sensor.

■ Digital Zoom

■ Dicom Simulation

Lamp original NP30LP / 100013543

Optional Remote control original 7N901053 / RD-469E / 7N900881 / RD-443E

Remote control original 100013630 / NP05CV

Order here: https://www.hcinema.de/lampen/shop-en.php?id=23411 2015 Discontinued (EOL) // Last update of the data: 2023-08-12


Created: 2015-08-21 12:40:49

Data

Status



Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.



More Details