

DX606VB – Multimedia Projector

Portable and Ready to Present

Small and stylish, the Optoma DX606VB produces great colors for life-like images, projects impressive brightness, and provides user-friendly features. Bright at 2500 ANSI lumens, the DX606VB is very easy to use in virtually any setting - from classrooms to conference rooms.



Features

- Bright at 2500 ANSI lumens with contrast ratio of 2200:1
- Portable at 4.4 pounds - convenient carrying case included
- Native XGA DLP by Texas Instruments
- Presentation-friendly IR remote control



Specifications

Display Type
Single 0.55" DMD DLP® Technology by Texas Instruments

Resolution
Native XGA (1024 x 768)

Maximum Resolution
SXGA+ (1400 x 1050)

Brightness (Typical)
2500 ANSI Lumens

Contrast Ratio
2200:1 (Full On/Full Off)

Lamp Life and Type
3000/2000 Hours (STD/Bright)
180W SHP

Throw Ratio
1.95 to 2.15:1 (Distance/Width)

Projection Distance
3.93' to 39.3 (1.2 to 12m)

Image Size (Diagonal)
27.49" to 303.12" (0.7 to 7.70m)

Aspect Ratio
4:3 Native, 16:9 Compatible

Audio
1-Watt Speaker

Horizontal Scan Rate
15 to 100 KHz

Vertical Refresh Rate
43 to 85 Hz

Offset
115%

Keystone Correction
±18° Vertical

Security
Kensington® Lock and Keypad Lock

Displayable Colors
16.7 Million

Uniformity
85%

Remote Control
Fully Featured IR Remote with Mouse Control

Computer Compatibility
SXGA+, SXGA, XGA, SVGA, VGA Resized, VESA, PC and Macintosh Compatible

Video Compatibility
NTSC, PAL, SECAM, SDTV (480i), EDTV (480p), HDTV (720p, 1080i)

Projection Lens
F=2.41-2.55, f=21.79-23.99mm, 1.1x Manual Zoom and Focus

User Controls
Complete On-Screen Menu Adjustments in 22 Languages

I/O Connectors
VGA-In, S-Video, Composite Video, Stereo Audio-In and USB

Projection Method
Front, Rear, Ceiling Mount, Table Top

Weight
4.4 lbs (2.0kg)

Power Supply
AC Input 100-240V, 50-60Hz, Auto-Switching

Operating Temperature

41 to 104°F (5 to 40°C), 80% Max Humidity

Dimensions (W x H x D)
10.2" x 2.9" x 7.4"
(259 x 73 x 188 mm)

Noise Level (STD/Bright)
28dB/30dB

Power Consumption
260 Watts (Max), <10 Watts (Standby)

Standard Accessories
AC Power Cord, VGA Cable, USB Cable, Remote Control, Batteries for Remote, Lens Cap, CD-ROM User's Manual, Quick Start Card and Warranty Card

Optional Accessories
Carrying Case, Ceiling Mount, VGA to Component Cable, S-Video Cable, Composite Video Cable and Panoview™ Series Screens

Warranty
1 Year Limited Parts and Labor, 90 Days on Lamp

UPC
796435 11 197 8

Accessory Part Numbers
Lamp: BL-FS180B
Remote: BR-5031N
Mount: BM-1015N
Case: BK-4019