Optoma EH515TST



Brief Introduction Beta 2.5 A brief introduction to the Optoma EH515TST. The standard portable DLP projector has an HDTV 1920 x 1080 resolution and a contrast of 10000:1. Includes a lens shift and keystone correction function, which provides freedom during installation. The projector is equipped with a microphone jack plug and 10W speakers, so no additional speakers are required for presentations or training courses. Thanks to the brightness of 5000 Ansi lumens, a picture width of 718 cm is possible. The projector can also handle slightly brighter rooms with a narrower image width (we recommend max. 479 cm). A smartphone with MHL connection can be connected directly to the MHL/HDMI port and transmit a 1080p / 60 Hz image mirroring (screen mirroring) while the smartphone is being charged at the same time. Even 1080P video signals and 3D are no problem for the projector. At just 28 decibels, the device is one of the quieter projectors. The model built in 2017 is no longer offered by Optoma.

Display Type

Black Level

Lens shift

Resolution

Application

Light Source

Light Life

Video Modes

1 x 0,65" DLP Chip HDTV 16/9 Ti Digital Light Processing Chip

Ansi-Lumen Contrast

ਹੁੰ ਹੋ 10000:1 full on/off ਹੁੰ 0,5000 min. Lumen ഗ്ഗ 2222 Lux (bei 200 cm Screen) റ്റ് 10000:1 full on/off ⁹ 0,222 min. Lumen

Vert.: +80% --55% Hori.: +/-10%

HDTV 1920 x 1080 2.073.600 Pixel

Pal, SECAM, NTSC, HDTV 720p, 1080i, 1080p, 3D, EDTV 480p, 576p

3D Compatibility Frame-Packing (Full HD 3D) | Side-by-Side | Top-and-Bottom

Frame Sequential (3D Ready)

Standard-Portabel | External training and company presentations, as well as product

presentations.

Wide screen width or rooms with plenty of light (over 200 lumens).

365W Lamp

Articel Nr.: SP.72109GC01 3000 h. 5000 h. in Eco Mode

Operating Costs

Focus Manual

Zoom No Zoom 1,8

Objective -

Throw Ratio 0,79:1



Audio 2 x 10W

2 x HDMI 1.4a mit MHL in 2 x D-sub 15pin in 1 x out

Cinch Video in

Mini Jack Audio in und out

USB Typ A in

Connections RS232C Din 9 pin in

RJ45 mit HDBaseT in

Display Port 3D Sync

12V Trigger out Mikrofon in

Ceiling Mounting Yes

Power 365 / 292W in Eco Mode

Size WxHxD 424 x 160 x 344 mm (16,7"x6,3"x13,5") 23,34 L/dm³

Operating Noise 28dB

Foot-Lamberts

Weight 6,10 kg / 13,45 lbs.

Keystone Vert.: +/-30°
Hori.: +/-30°
80%

Frequenz H-sync: 15,3-91,14 kHz V-sync: 24-85 Hz

206 fL / max. 718 cm screen width

706 cd/m²

Real Full HD 3D

■ Full HD 1080P compatible

■ Lens shift Funktion

■ Eco Mode

Kensington Slot

Password protection

Features ■ BrilliantColor™

■ PJLink™

Optional Wi-Fi network compatible.

Lan network compatible.Short-throw projector

■ Crestron®-Software compatible.

■ Dicom Simulation

Lamp original SP.72109GC01 / BL-FU365A

Remote control original BR-3070L, SP.72101GC01

Order here: https://www.hcinema.de/lampen/shop-en.php?id=23437

2017 Discontinued (EOL) // Last update of the data: 2023-09-20

Created: 2017-11-20 15:55:18

Data

Optional

Status











16/9 screen width:200 cm

Key: 91 cm Shift: 90 cm

Key: 91 cm Shift: -62 cm

Key: 91 cm Shift: 20 cm Screen:1 Gain

Cey: 91 cm Shift: 20 cm

More Details



HCinema

https://www.projector-database.com/pro/optomaeh515tst-en.html

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.