

DV11 Home Theater Projector

Your Ultimate Choice

The evolution of home entertainment continues to move forward. The Optoma DV11, the next progression of the award-winning DV10, is a fully digital home theater projector with integrated DVD player. The DV11's slot-in DVD player, enhanced 5-watt speakers and brilliant theater-quality projection turns any space into an instant home theater setting. Easy-to-use features make the Optoma DV11 ideal for a wide range of home entertainment options on a large screen.

Features

- All-in-one instant theater projector with built-in DVD player and speakers
- Slot-in DVD drive plays DVDs, MP3 audio cds, even JPEG files
- Enhanced two 5-watt speakers and ceiling mountable form factor
- Bright 1600 ANSI lumens with 2200:1 contrast ratio
- Native 16:9 with support of 4:3 and LBX formatted DVD videos
- Optimized DVD and projector settings provide true widescreen cinema-quality performance

Specifications

Brightness

1600 ANSI Lumens

Supported Resolution

480p, 720p, 1080i, SVGA, XGA, SXGA, VGA, SXGA+, VESA, PC and Macintosh Compatible

Contrast Ratio

2200:1 (Full On/Off)

Lamp Life

2000 Hours

Lamp Type

180W User Replaceable

Display Type

Single 0.55" DDR DLP® Technology by Texas Instruments

Throw Ratio

1.36 – 1.50 (Distance/Width)

Offset

115%

Projection Distance

4.9' to 32.8'

Image Size

48" to 359"

Aspect Ratio

Native 16:9, 4:3 and 5:4 Compatible, Letterbox Standard

Projection Lens

1.1:1 Manual Zoom and Focus

Displayable Colors

16.7 Million

Video Compatibility

NTSC, PAL, SECAM, SDTV (480i), EDTV (480p), 576i/p, HDTV (720p, 1080i)

Media Compatibility

DVD, VCD, JPEG, Kodak picture CD, DVD Region Code: 1

Audio Compatibility

MP3, WMA, Audio CD, Dolby Digital

Horizontal Refresh Rates

31.5 to 100kHz

Vertical Refresh Rates

43 to 120 Hz

Keystone Correction

± 15° vertical

Audio

Two 5-Watt internal speaker

I/O Connectors

VGA-In, S-Video, Composite Video, Stereo Audio-In, Stereo Audio-Out, Coaxial Audio-Out

Projection Method

Front, Rear, Table Top, Ceiling Mount

Uniformity

85%

Weight

8.5lbs

Dimensions (W x H x D)

15" x 5.5" x 10.9"
(381 x 140 x 277 mm)

Noise Level

34dB/28dB

Power Supply

100-240 Volts, 50-60Hz

Power Consumption

245W ± 10%, <12W Standby Mode

Standard Accessories

AC Power Cord, Composite Cable, VGA to Component Adapter, Lens Cap, Remote Control, Batteries for Remote, User's Manual, Carrying Case, Quick Start Guide and Warranty Card

Optional Accessories

Panoview GrayWolfII™ Portable-Lift Screens, Dolcen Kreiling™ 50-Watt Subwoofer, BERING Mount and Gold Service Warranty

Warranty

2 Years on Projector,
1 Year on DVD Module,
90 Days on Lamp

UPC

796435 24 167 4

