



**Revitalisierung von Nachhaltigkeit und
Imagequalität in Klassenzimmern und am
Arbeitsplatz**

PT-MZ782

Die Serie umfasst die WUXGA-Modelle PT-MZ882 (8.200 lm11), PT-MZ782 (7.500 lm11) und PT-MZ682 (6.500 lm) mit einer verfeinerten Multi-Laser-Drive-Engine für die optimale Balance zwischen hoher Helligkeit, lebendigen Farben und wartungsarmem Betrieb. *1 Messung, Messbedingungen und Notationsmethode entsprechen den internationalen Normen ISO/IEC 21118: 2020. Der Wert entspricht dem Durchschnitt aller Produkte beim Versand.

Key Features

Umweltbewusstes Design mit recycelten Materialien

Hell und scharf für angenehme Sicht

Optimiertes Arbeiten/niedrige und effiziente UX



PT-MZ782

<https://eu.connect.panasonic.com/de/products/projectors/pt-mz782>

Panel Size	19.3 mm (0.76 in) diagonal (16:10 aspect ratio)
Display Method	Transparent LCD panel (x 3, R/G/B)
LCD Panel	
Projector type	LCD projectors
Drive Method	Active matrix
Pixels	2,304,000 (1920 x 1200) pixels x 3
Light Source	Laser diodes
Light output 1, 2	7,500 lm
Time until light output declines to 50 %³	20,000 hours (NORMAL/QUIET), 24,000 hours (ECO)
Auflösung	WUXGA (1920 x 1200 pixels)
Contrast ratio 2	3,000,000:1 (Full On/Full Off) (When [PICTURE MODE] is set to [DYNAMIC] and [DYNAMIC CONTRAST] is set to [1] or [2]. HDMI™ signal input)
Lens	Powered zoom (throw ratio 1.61–2.76:1), powered focus F = 1.7–2.3, f = 26.8–45.5 mm (for supplied lens; optional lenses also available)
Screen Size (Diagonal)	1.02–10.16 m (40–400 in), 1.52–10.16 m (60–400 in) with the ET-ELW22, 2.54–10.16 m (100–400 in) with the ET-ELU20, 16:10 aspect ratio
Center-to-corner zone ratio²	85 %
Lens shift Vertical (From the origin point of the lens mounter)	±67 % (powered), ±60 % (with ET-ELW22), ±50 % (with ET-ELU20) (TBD)
Keystone Correction Range	Vertical: ±25 ° (±22 ° with ET-ELW21/ET-ELW22); (±25 ° with ET-ELW20/ET-ELT22/ET-ELT23); (±5 ° with ET-ELU20), Horizontal: ±30 ° (±15 ° with ET-ELW21/ET-ELW22); (±30 ° with ET-ELW20/ET-ELT22/ET-ELT23); (0 ° with ET-ELU20)
Installation	Ceiling/floor, front/rear, free 360-degree installation
Lens shift Horizontal (From the origin point of the lens mounter)	±35 % (powered), ±30 % (with ET-ELW22), ±24 % (with ET-ELU20) (TBD)
Audio In	M3 stereo mini-jack x 1
Monitor Out	D-sub HD 15-pin (female) x 1 (RGB/YPBPR/YCBCR)
Remote 1 In	M3 stereo mini-jack x 1 for wired remote control
Remote 2 In	D-sub 9-pin (female) x 1 for external control (parallel)
Terminals	
Computer In	D-sub HD 15-pin (female) x 1 (RGB/YPBPR/YCBCR)
MULTI SYNC OUT	D-sub 9-pin (male) x 1 for link control
HDMI™ IN	HDMI™ x 3 (Deep Color, compatible with HDCP 2.3, 4K/60p signal input ⁴), CEC supported
SERIAL/MULTI SYNC IN	D-sub 9-pin (female) x 1 for external control/link control (RS-232C compliant)
LAN	RJ-45 x 1 for network connection, 10Base-T, 100Base-TX (Compatible with PLink™ [Class 2], Art-Net)
DC Out	USB Type A x 1 (for power supply, DC 5 V, 2 A)
Audio Out	M3 stereo mini-jack x 1
DIGITAL LINK/LAN	RJ-45 x 1 for network and DIGITAL LINK connection (video/network/serial control) (HDBase™ compliant), 100Base-TX (Compatible with PLink™ [Class 2], Art-Net, HDCP 2.3, Deep Color, 4K/60p ⁴ , 5 signal input)
Power Supply	AC 100–240 V, 50 Hz/60 Hz
NORMAL	385 W (AC 100–120 V), 365 W (AC 200–240 V) (TBD)
ECO	280 W (AC 100–120 V), 270 W (AC 200–240 V) (TBD)
QUIET	275 W (AC 100–120 V), 265 W (AC 200–240 V) (TBD)
Maximum power consumption 6	428 W (4.7–2.3 A) (450 VA) (Power consumption is 408 W at AC 200–240 V) (TBD)
On-mode power consumption (Operating mode) 6	
Abmessung (B x H x T)	561 x 224 x 439 mm (22 3/32" x 8 13/16" x 17 9/32") (With legs at shortest position, including lens and protruding parts)
Operating Environment	Operating temperature: 0–45 °C (32–113 °F) ⁸ , operating humidity: 10–80 % (no condensation)
Cabinet Materials	Molded plastic
Applicable Software	Logo Transfer Software, Multi Monitoring & Control Software, Smart Projector Control for iOS/Android™, Geometry Manager Pro 9
Filter	Included (Estimated maintenance time: approx. 20,000 hours)
Operation noise 2	33 dB (NORMAL/ECO), 27 dB (QUIET) (TBD)
Weight 7	Approx. 18.6 kg (41.0 lbs) (with supplied lens)
Notification	Please note for internal use only until the official product release.