

Panasonic PT-RQ7L

PANASONIC PT-RQ7L



A brief introduction to the Panasonic PT-RQ7L. The DLP laser projector has an HDTV 1920 x 1080 resolution and a contrast of 15000:1. Due to the laser, the projector is specified with 20000 hours of light life, which is over 13.7 years if enjoyed for four hours a day. A picture width of up to 880 cm is possible, if the picture width is smaller (we recommend max. 587 cm), rooms with residual light are also no problem. If the image width is not sufficient, the projector offers integrated edge blending software, which allows several projectors to project a large image together. The projector has optional Airplay and Miracast screen mirroring support, which enables direct playback of videos in high resolution and surround sound from smartphones, tablets and PCs with Android, Windows or iOS via Wi-Fi. Furthermore, the projector can play 1080P and 4K (compressed) without any problems and can even project Blu-rays onto the ceiling using 360° projection.



1 x 0,65" DLP Chip
HDTV 16/9 Ti Digital Light Processing Chip

Projector

7500
15000:1 full on/off
0,5000 min. Lumen

Screen

3333 Lux (bei 200 cm Screen)
15000:1 full on/off
0,222 min. Lumen

Brief Introduction Beta 2.5

Display Type

Ansi-Lumen

Contrast

Black Level
Offset

Resolution

Video Modes

Application

Light Source

Light Life

Operating Costs

Focus

Zoom

Objective

Throw Ratio

HDTV 1920 x 1080

2.073.600 Pixel

UHD (4K2K) 3840 x 2160 compressed

Pal, SECAM, NTSC, HDTV 720p, 1080i, 1080p, 4K UHD (komprimiert), EDTV 480p, 576p

Stationary | Permanent installation in the training room and meeting room as well as the conference room.

Very large screen width and rooms with plenty of light and shaded daylight.

Laser

20000 h. / 24000 h. in Eco Mode

0,00 € Laser

Powered

Powered

optional

optional



Audio	-	16/9 screen width:200 cm Screen:1 Gain
Connections	2x HDMI (Deep Color, HDCP 2.3, 4K/60p input5) D-sub 9-pin in und out (RS-232C compliant) Audio Mini Jack in und out (for wired Remote) Cinch Video in Cinch Stereo in Mini Jack Audio in und out USB Type A (for power supply, DC 5 V, 2 A) RS232C Din 9 pin in RJ45 in HDBaseT (100Base- TX) Open slot for function boards, Intel® SDM	
Ceiling Mounting	Yes	
Power	720W Max / 440W in Eco Mode	
Size WxHxD	498 x 170 x 440 mm (19,6"x6,7"x17,3") 37,25 L/dm³	
Operating Noise	36 / 33 dB in Eco Mode	

Weight	18,00 kg / 39,68 lbs.
Keystone	-
Illumination	-

Frequenz	-
----------	---

Foot-Lamberts	310 fL / max. 880 cm screen width 1062 cd/m²
Features	■ Full HD 1080P compatible
	■ User logo
	■ Eco Mode
	■ Kensington Slot
	■ Warping
	■ 360° installable
	■ 24/7 continuous operation capable
	■ Edge Blending
	■ PJLink™
	■ Lan network compatible.

- Crestron®-Software compatible.
- Multi Monitoring & Control Software,
- Projector Network Setup Software,
- Real-Time Tracking Projection-Mapping System11, Geometry Manager Pro,
- Smart Projector Control for iOS/Android™
- Crestron XiO Cloud™
- Crestron Connected™ V2

Optionaler Zubehör

	Fernbedienung Original	N2QAYA000256	52,06 €
	Objektiv Gebraucht Original	ET-DLE450	1.482,23 €
	Objektiv Gebraucht Original	ET-DLE350	3.431,52 €
	Objektiv Gebraucht Original	ET-DLE250	1.898,73 €
	Objektiv Original	ET-DLE170	1.440,02 €
	Objektiv Gebraucht Original	ET-DLE150Z	1.839,23 €
	Objektiv Original	ET-DLE150	3.431,52 €
	Objektiv Original	ET-DLE105	5.140,84 €
	Objektiv Gebraucht Original	ET-DLE085	2.811,38 €
	Objektiv Original	ET-DLE060	4.005,06 €

	Objektiv Original	ET-DLE055	4.092,54 €
	Objektiv Original	ET-DLE035	9.170,01 €
	Wechselobjektiv Original	ET-DLE020	14.908,60 €
	Deckenhalterung Länge 225 mm	Halterung45	85,80 €

Optional Lenses					
Name	Ratio	Distance	Shift V	Shift H	Zoom
Zoom Optional Lenses					
ET-DLE450	5.33-8.53:1	10.7-17.1 m	55-18%	30-10%	Powered
ET-DLE350	3.56-5.42:1	7.1-10.8 m	55-18%	30-10%	Powered
ET-DLE250	2.26-3.6:1	4.5-7.2 m	55-18%	30-10%	Powered
ET-DLE170	1.71-2.4:1	3.4-4.8 m	55-18%	30-10%	Powered
ET-DLE150	1.29-1.88:1	2.6-3.8 m	55-18%	30-10%	Powered
ET-DLE105	0.97-1.32:1	1.9-2.6 m	55-18%	28-10%	Powered
ET-DLE085	0.78-0.97:1	1.6-1.9 m	55-18%	28-10%	Powered
ET-DLE060	0.6-0.8:1	1.2-1.6 m	44-18%	19-10%	Powered
ET-DLE020	0.28-0.3:1	0.6-0.6 m	55-18%	10-20%	Powered
Fix Optional Lenses					
ET-DLE055	0.78:1	1.6 m			No Zoom
ET-DLE035	0.38:1	0.8 m			No Zoom

Status

2024 Current model // Last update of the data: 2025-02-17
Created: 2024-02-28 14:46:41



More Details



HCinema

<https://www.projector-database.com/pro/panasonicptrq7l-en.html>

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.