

Panasonic PT-RZ6L

PANASONIC PT-RZ6L



The stationary PT-RZ6L Laser DLP has 6500 Ansi-Lumen, a contrast of 15000:1 and a WUXGA 1920 x 1200 resolution. The manufacturer Panasonic specifies a service life of 20000 hours, which is over 13.7 years with a daily viewing time of 4 hours. 819 cm picture width the projector will be able to illuminate well. Rooms with residual light can be created by the projector with a smaller image width, we recommend a maximum of 546 cm. If the image width is not sufficient, the projector offers integrated edge blending software, which allows several projectors to project a large image together. The model optionally recognizes Airplay, Miracast Screen Mirroring signals, so it is possible to play videos with high resolution and surround sound directly via WLAN from a smartphone, tablet or PC (Android, Windows and iOS). Even 1080P and 4K (compressed) video signals are no problem for the projector, which can even project Blu-rays onto the ceiling thanks to 360° projection.

Brief Introduction

Beta 2.5

Display Type



1 x 0,67" DLP Chip

WUXGA 16/9 Ti Digital Light Processing Chip

Ansi-Lumen

6500

2889 Lux (bei 200 cm Screen)

Contrast

15000:1 full on/off

15000:1 full on/off

Black Level

0,4333 min. Lumen

0,193 min. Lumen

Offset

-

Resolution

WUXGA 1920 x 1200

2.304.000 Pixel

Video Modes

UHD (4K2K) 3840 x 2160 compressed

Pal, SECAM, NTSC, HDTV 720p, 1080i, 1080p, 4K UHD (komprimiert), EDTV 480p, 576p

Application

Stationary | Permanent installation in the training room and meeting room as well as the conference room.

Very large screen width and rooms with plenty of light and shaded daylight.

Light Source

Laser

Light Life

20000 h. / 24000 h. in Eco Mode

Operating Costs

0,00 € Laser

Focus

Powered

Zoom

Powered

Objective

optional

Throw Ratio

optional

Audio

-



Connections	2x HDMI (Deep Color, HDCP 2.3, 4K/60p input5)
	D-sub 9-pin in und out (RS-232C compliant)
	Audio Mini Jack in und out (for wired Remote)
	Cinch Video in
	Cinch Stereo in
	Mini Jack Audio in und out
	USB Type A (for power supply, DC 5 V, 2 A)
	RS232C Din 9 pin in
	RJ45 in
	HDBaseT (100Base- TX)
Ceiling Mounting	Open slot for function boards, Intel® SDM
Power	Yes
Size WxHxD	620W Max / 340W in Eco Mode
Operating Noise	498 x 170 x 440 mm (19,6"x6,7"x17,3") 37,25 L/dm³
	35 / 32 dB in Eco Mode

Weight	18,00 kg / 39,68 lbs.
Keystone	-
Illumination	-

Frequenz	-
----------	---

Foot-Lamberts	268 fL / max. 819 cm screen width
	918 cd/m²
	■ Full HD 1080P compatible
	■ User logo
	■ Eco Mode
	■ Kensington Slot
	■ Warping
	■ 360° installable
	■ 24/7 continuous operation capable
	■ Edge Blending

Features	■ PJLink™
	■ Lan network compatible.
	■ Crestron®-Software compatible.
	■ Multi Monitoring & Control Software,
	■ Projector Network Setup Software,
	■ Real-Time Tracking Projection-Mapping System11, Geometry Manager Pro,
	■ Smart Projector Control for iOS/Android™
	■ Crestron XiO Cloud™
	■ Crestron Connected™ V2

Optionaler Zubehör

	Fernbedienung Original	N2QAYA000256	52,06 €
	Objektiv Gebraucht Original	ET-DLE450	1.482,23 €
	Objektiv Gebraucht Original	ET-DLE350	3.431,52 €
	Objektiv Gebraucht Original	ET-DLE250	1.898,73 €
	Objektiv Original	ET-DLE170	1.440,02 €
	Objektiv Gebraucht Original	ET-DLE150Z	1.839,23 €
	Objektiv Original	ET-DLE150	3.431,52 €
	Objektiv Original	ET-DLE105	5.140,84 €
	Objektiv Gebraucht Original	ET-DLE085	2.811,38 €
	Objektiv Original	ET-DLE060	4.005,06 €
	Objektiv Original	ET-DLE055	4.092,54 €

	Objektiv Original	ET-DLE035	9.170,01 €
	Wechselobjektiv Original	ET-DLE020	14.908,60 €
	Deckenhalterung Länge 225 mm	Halterung45	85,80 €

Optional Lenses					
Name	Ratio	Distance	Shift V	Shift H	Zoom
Zoom Optional Lenses					
ET-DLE450	5.36-8.58:1	10.7-17.2 m	50-16%	28-10%	Powered
ET-DLE350	3.58-5.45:1	7.2-10.9 m	50-16%	28-10%	Powered
ET-DLE250	2.27-3.62:1	4.5-7.2 m	50-16%	28-10%	Powered
ET-DLE170	1.71-2.41:1	3.4-4.8 m	50-16%	28-10%	Powered
ET-DLE150	1.3-1.89:1	2.6-3.8 m	50-16%	28-10%	Powered
ET-DLE105	0.98-1.32:1	2-2.6 m	50-16%	28-10%	Powered
ET-DLE085	0.78-0.98:1	1.6-2 m	50-18%	28-10%	Powered
ET-DLE060	0.6-0.8:1	1.2-1.6 m	40-16%	19-10%	Powered
ET-DLE020	0.28-0.3:1	0.6-0.6 m	50-16%	10-20%	Powered
Fix Optional Lenses					
ET-DLE055	0.79:1	1.6 m			No Zoom
ET-DLE035	0.38:1	0.8 m			No Zoom

Status

2024 Current model // Last update of the data: 2025-02-17
Created: 2024-02-28 15:02:27



More Details



HCinema

<https://www.projector-database.com/pro/panasonicptrz6l-en.html>

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.