Paramount SMART 7500



Brief Introduction

Beta 2.5

Display Type

Ansi-Lumen

Contrast Black Level

Offset

Resolution

Video Modes

Application

Light Source Light Life

Operating Costs

Focus

Zoom

Objective

Throw Ratio

Connections

Audio

Ceiling Mounting

Power Size WxHxD **Operating Noise**

Weight Keystone Illumination

Frequenz

Foot-Lamberts

Features

Status

Brief introduction of the Paramount SMART 7500. The standard portable LCD projector has a VGA 640 x 480 resolution and a contrast of 800:1 (peak value). The service life of the lamp is up to 6000 hours, which is over 8.2 years with a daily viewing time of 2 hours. An image width of up to 337 cm is possible as the projector has 1500 Ansi lumens. However, if room light is available, the picture should be a maximum of 225 cm wide. Playing 1080P is also no problem for the projector. The model built in 2013 is no longer offered by Paramount.

ω500 Lux (bei 200 cm Screen)

9 800:1(Peak Value) 0,627 min. Lumen

1 x 7" LCD TFT Panel

VGA 4/3 Liquid Crystal Display

1500 / (Peak Value) 800:1(Peak Value)

1,8750 min. Lumen

VGA 640 x 480 307.200 Pixel

XGA 1024 x 768 compressed

Pal, SECAM, NTSC, HDTV 720p, 1080i, 1080p EDTV 480p, 576p

Standard-Portabel | External training and company presentations, as well as product

Small screen width, rooms with very little ambient light below 100 lumens.

6000 h.

Manual

No Zoom

F=2.8 f=170mm

1 x 3W Mono

HDMI in D-sub 15 pin in

S-Video in Cinch Video in

Scart in

200W

Lux:500 Lux Room light max.: 100 Lux Candela pro m²:158 cd/m² Foot-Lamberts:46 fL 4/3 screen width:200 cm Screen:1 Gain

A R A M O C N

46 fL / max. 337 cm screen width

158 cd/m²

■ Full HD 1080P compatible

2013 Discontinued (EOL) // Last update of the data: 2023-08-04

Data

More Details



Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.