



PLANAR PD4010 480P SPECIALTY HOME THEATER PROJECTOR



At 2500:1 ratio contrast and 900 lumens, this is a projector your budget can really get behind, without compromise.

SIGNAL COMPATIBILITY

Video Support: HDMI and DVI with HDCP for digital video, Component and RGB HDTV (1080i, 720p), Component and RGB EDTV (576p, 480p), Component, Composite and S-Video SDTV (576i, 480i, RGB SCART with adapter, NTSC/NTSC 4.43, PAL (B,G)/(D,K)/I/M/N, SECAM (B,G)/(D,K), L

Computer Support: Digital and Analog up to 1024x768 @ 60Hz, Macintosh®

Communication: RS-232 (discrete commands) and USB (SW upgrades), IR remote, on-board keypad

CONNECTIVITY

- (1) DVI-D: HDTV RGB and Component, DVI (Digital Visual Interface) with HDCP (High Bandwidth Digital Content Protection), HDMI via included adapter
- (1) Component (RCA): HDTV, EDTV, SDTV, SCART RGBS: RGBS via Component and Composite inputs (adapter not included)
- (1) RGB (HD15): HDTV, Computer (Hsync 15~70kHz, Vsync 50~85Hz)
- (1) S-Video: SDTV
- (1) Composite: SDTV
- (1) 3.5mm mini jack: 12V screen trigger (0.25 Amps)
- (1) 3.5mm mini jack: IR input
- (1) 9 Pin D-sub RS-232
- (1) USB type B: SW upgrades

PERFORMANCE

Microdisplay: Texas Instruments DLP® DarkChip2™ 0.55 480p 12° DDR DMD

Native Resolution: 854 x 480 (409,920 pixels)

Aspect Ratios: Native, 16:9, Letterbox, 4:3, Anamorphic compatible

Projection Lens: All glass, F/2.50, f=24.0~30.1 mm, 1:16x manual zoom

Throw Ratio: 2.1 - 2.5 (distance/width)

Lens Shift: 138% fixed offset

Video Lumens: 900 ANSI max

Contrast Ratio: 2500:1 (max full on/full off)

Cooling Performance: High efficiency adaptive voltage side-to-side cooling with low system acoustic noise level (30dBA) and low light pollution cabinet

Projection Modes: Front, Rear, Ceiling (front/rear)

Keystone (digital): +/-15° (vertical)

Lamp: User replaceable 180/200W HPM (selectable), 4000 hour lifetime*

Video Processing: TI DDP2000 video with Motion-Adaptive De-Interlacing, rich color processing and noise reduction

Calibration: Full RGB gain/offset control (White Balance), Gamma, Contrast, Color Temp (Presets), Brightness

GENERAL

Dimensions: 12.4" (315mm) L x 13.6" (347mm) W x 5.8" (147mm) H

Weight: ~8 lb (3.6 kg)

Operating Temperature: 50° F (10° C) - 95° F (35° C)

Operating Altitude: Sea Level - 7,500 Ft (2,300m)

Operating Humidity: 5% - 90% non-condensing

Universal Power Supply: 100V - 240V at 50-60Hz (auto-ranging), true soft power

Regulatory: FCC Part 15 Class B, CE Class B, UL, cUL, CB, RoHS, WEEE, local conformances as required

Menu Languages: English, French, Italian, German, Spanish, Portuguese, Swedish, Dutch, Russian, Norwegian, Simplified Chinese, Traditional Chinese, Korean

Planar reserves the right to modify the specifications at any time without notice
*Actual lamp life will vary depending on the environmental condition of the application

CORPORATE HEADQUARTERS

Planar Systems, Inc. | 1195 NW Compton Drive | Beaverton, OR | 97006 | USA | 1-866-475-2627

EUROPEAN HEADQUARTERS

Planar Systems, Inc. | Olarinluoma 9 | PO Box 46 | FIN-02201 | Espoo, Finland | 358-9-42-001