



Brief Introduction Beta 2.5

Display Type

Ansi-Lumen Contrast **Black Level**

Offset

Resolution

Video Modes

Application

Light Source

Light Life

Operating Costs

Focus

Zoom

Objective

Throw Ratio

Audio

Connections

Ceiling Mounting

Power

Size WxHxD

Operating Noise

Weight Keystone Illumination

Frequenz

Foot-Lamberts

212 cd/m²

The Premier PD X650 DLP projector has 2000 Ansi lumens, a contrast of 2000:1 and an XGA 1024 x 768 resolution. An image width of up to 389 cm is possible. However, the image should be smaller in room light. We recommend max. 259 cm. This model is no longer offered by Premier.

ω667 Lux (bei 200 cm Screen)

2000:1 full on/off 0,334 min. Lumen

1 x 0,55" DDR DLP Chip XGA 4/3 Ti Digital Light Processing Chip

2000 2000:1 full on/off 1,0000 min. Lumen

XGA 1024 x 768

786.432 Pixel PAL, SECAM, NTSC, HDTV 720p, 1080i, EDTV 480p, 576p

Standard-Portabel | External training and company presentations, as well as product

presentations.

Medium screen width or rooms with little light, max. 100 lumens.

200W Lamp 2000 h. 3000 h. in Eco Mode

Manual 1,2

Manual

1 x 2W

D-sub 15pin in

S-Video in Cinch Video in RS232C in USB in

Mini Jack Audio in

Yes 280W

253 x 97 x 201 mm (10"x3,8"x7,9") 4,93 L/dm3

36 / 34 dB in Eco Mode

Lux:**667** Lux Room light max.:133 Lux Candela pro m²:212 cd/m² Foot-Lamberts:62 fL 4/3 screen width:200 cm

Screen:1 Gain

2,70 kg / 5,95 lbs. Vert.: +/-15°

80%

62 fL / max. 389 cm screen width

Features

Status Data Eco Mode

■ 4-segment RGBW colour wheel.

2007 Discontinued (EOL) // Last update of the data: 2023-08-04

More Details





Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.