Prolight PLF782AX





Brief Introduction

Beta 2.5

3 x 0,7" LCD TFT Panel

Display Type Ansi-Lumen

1900

Black Level Offset

Contrast

Resolution

Video Modes

Application

Light Source Light Life

Operating Costs

Focus

Zoom

Objective

Throw Ratio

Audio

Connections

Ceiling Mounting Power

Size WxHxD

Operating Noise

Weight 3,10 kg / 6,83 lbs. Keystone

Illumination H-sync: 15-80 kHz

Frequenz V-sync: 43-85 Hz

59 fL / max. 380 cm screen width Foot-Lamberts 202 cd/m²

The Prolight PLF782AX LCD projector has 1900 Ansi lumens, a contrast of 450:1 and an XGA 1024 x 768 resolution. The projector can illuminate an image width of up to 380 cm well thanks to the 1900 Ansi lumens. In room light, however, the image width should ideally be less than 253 cm. It is no longer offered by the manufacturer Prolight.

ω633 Lux (bei 200 cm Screen)

450:1 full on/off 1,416 min. Lumen

XGA 4/3 Liquid Crystal Display

450:1 full on/off 4,2222 min. Lumen

XGA 1024 x 768

SXGA 1280 x 1024 compressed

PAL, SECAM, NTSC

Standard-Portabel | External training and company presentations, as well as product

presentations.

786.432 Pixel

Small screen width, rooms with very little ambient light below 100 lumens.

180W Lamp 2000 h.

Manual

Manual 1,23

F=1,7-2,1 f=26-32 mm

1,8-2,3:1


1 x 2W

D-sub 15pin in Cinch Video in S-Video in Mini Jack

USB RS232C

37dB

Yes 230W 233 x 93 x 297 mm (9,2"x3,7"x11,7") 6,44 L/dm3



Features Status Data

- Discontinued (EOL) // Last update of the data: 2023-08-04

More Details



HCinema
https://www.projector-database.com/pro/prolightPLF782AX-en.html

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.