Provox HPV320



Brief Introduction Beta 2.5

The Provox HPV320 standard portable projector has 2000 Ansi lumens, a contrast of 2500:1 and a WPAL 1024 x 576 resolution. 2000 Ansi lumens ensure that a picture width of 454 cm is also possible. However, if room light is available, the picture should be max. 303 cm wide. It is no longer offered by the manufacturer Provox.

Display Type

Ansi-Lumen Contrast Black Level Offset

Resolution

Video Modes Application

Light Source

Light Life

Operating Costs

Focus

Objective

Zoom

Audio

Weight

Frequenz

Features Status

Data

Throw Ratio

Connections

Ceiling Mounting Power

Size WxHxD Operating Noise 2000

2500:1 full on/off 0.8000 min. Lumen

WPAL 1024 x 576

ω889 Lux (bei 200 cm Screen) 2500:1 full on/off

ក្លី 2500: ការកា 5... ַ 0,356 min. Lumen

Lux:889 Lux

16/9 screen width:200 cm

Screen:1 Gain

Room light max.:178 Lux

Candela pro m²:284 cd/m² Foot-Lamberts:83 fL

489.824 Pixel PAL, SECAM, NTSC, HDTV 720p, 1080i, EDTV 480p, 576p

Standard-Portabel | External training and company presentations, as well as product

presentations.

Medium screen width or rooms with little light, max. 100 lumens.

2000 h. 4000 h. in Eco Mode

Manual

Manual

DVI-I S-Video in

Cinch Video in

Yes

333 x 123 x 295 mm (13,1"x4,8"x11,6") 12,08 L/dm³

32,7 / 30 dB in Eco Mode

3,60 kg / 7,94 lbs.

Keystone Illumination

> H-sync: 15-82 kHz V-sync: 50-85 Hz

Foot-Lamberts 83 fL / max. 454 cm screen width

- Discontinued (EOL) // Last update of the data: 2023-08-04

284 cd/m² **■** Eco Mode





More Details

