Pyle PRJLE60







Brief Introduction Beta 2.5

Display Type

Ansi-Lumen

Contrast

The PRJLE60 LCD projector from Pyle has 150 Ansi lumens and a VGA 640 x 480 resolution. As Pyle specifies the brightness of the projector in lumens, we have calculated an approximate Ansi lumen value in this case. The projector will be able to illuminate a picture width of 107 cm well. However, if room light is available, the image width should ideally not exceed 71 cm. This model is no longer available from Pyle.

ω 50 Lux (bei 200 cm Screen)

1 x 3,2" LCD TFT Panel VGA 4/3 Liquid Crystal Display

150 / 2500 Lumen

50W LED

Black Level

Offset

VGA 640 x 480 Resolution 307.200 Pixel

Video Modes PAL, SECAM, NTSC, HDTV 720p, 1080i, EDTV 480p, 576p Game-Portabel | Very portable, small-screen projections. Application Very narrow picture width and rooms with very little light.

Light Source

Light Life

Operating Costs 0,00 € LED

Manual **Focus**

No Zoom Zoom

Objective f=125mm

Throw Ratio 1.92:1

Audio Stereo

Power Size WxHxD **Operating Noise**

Connections D-sub 15 pin in Ceiling Mounting

Weight Keystone Vert.: +/-15° Illumination

Frequenz

5 fL / max. 107 cm screen width Foot-Lamberts


17 cd/m²

Features

Status Data

2011 Discontinued (EOL) // Last update of the data: 2024-06-04

384 cm (no Zoom) Lux:50 Lux Room light max.:10 Lux Candela pro m²:17 cd/m² Foot-Lamberts:5 fL 4/3 screen width:200 cm Screen:1 Gain



More Details



Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.