Ricoh PJ S2130







Brief Introduction Beta 2.5

Display Type

Ansi-Lumen Contrast Black Level

Offset

Resolution

Video Modes

Application

Light Source Light Life

Operating Costs

Zoom

Focus

Objective

Throw Ratio

Audio

Connections

Ceiling Mounting

Power Size WxHxD 258 / 203W in Eco Mode

286 x 100 x 208 mm (11,3"x3,9"x8,2") 5,95 L/dm3 Operating Noise

With the PJ S2130, manufacturer Ricoh offers a standard portable DLP projector with SVGA 800 x 600 resolution and a contrast of 2200:1. The projector can illuminate an image width of up to 461 cm thanks to its 2800 Ansi lumens. In room lighting, however, the image width should ideally be less than 307 cm. The model built in 2012 is no longer offered by Ricoh.

ω933 Lux (bei 200 cm Screen)

2200:1 full on/off 0,425 min. Lumen

1 x 0,55" DLP Chip

SVGA 4/3 Ti Digital Light Processing Chip

2800 2200:1 full on/off

1,2727 min. Lumen

SVGA 800 x 600 480.000 Pixel

Pal, SECAM, NTSC, HDTV 720p, 1080i, EDTV 480p, 576p

Standard-Portabel | External training and company presentations, as well as product

presentations.

Medium screen width or rooms with little light, max. 100 lumens.

200W Lamp Articel Nr.: 308883

3000 h. 4000 h. in Eco Mode

Manual

Manual

2W Mono

HDMI in

D-sub 15pin in und out


Cinch Video in Cinch Stereo in S-Video in

Mini Jack Audio in und out

USB Typ B in

RS232C Din 9 pin in

37 / 32 dB in Eco Mode



Weight 2,50 kg / 4,41 lbs.

Keystone -Illumination -

Frequenz -

Features

More Details

Status

Foot-Lamberts 87 fL / max. 461 cm screen width

298 cd/m² ■ Freeze

Eco Mode

2012 Discontinued (EOL) // Last update of the data: 2023-09-25

Created: 2013-06-17 12:43:49

Data





Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.