Runco Image Pro digital 600

Display Type

3 x 7" liquid-cooled CRT

Ansi-Lumen

522 600 Lumen

φ169 Lux (bei 203 cm Screen) creen

Black Level Offset

Contrast

Resolution

Video Modes

Application Light Source NTSC, PAL, SECAM Pal 60 NTSC 4,43 CRT Projection | Very narrow picture width and rooms with very little light.

CRT Röhre ca. 10000 - 20000 h. (je nach Anwendung)

Light Life

Operating Costs

Focus

Manual Zoom

Objective

Throw Ratio

Audio

Connections Ceiling Mounting Power

Size WxHxD Operating Noise

Lux:169 Lux Room light max.:34 Lux Candela pro m²:55 cd/m² Foot-Lamberts:16 fL 4/3 screen width: 203 cm Screen:1 Gain

Weight

38,00 kg / 83,78 lbs.

Keystone Illumination

Frequenz

H-sync: 15,75 kHz V-sync: 50-60 Hz

Foot-Lamberts

16 fL / max. 199 cm screen width

55 cd/m²

Features

Status

Data

- Discontinued (EOL) // Last update of the data: 2023-08-04

More Details





https://www.projector-database.com/pro/runcocinemaprodigital600-en.html

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.