## Sanyo PLC 9000E/A/L









**Brief Introduction** Beta 2.5

> are no longer any replacement lamps for the projector, neither originals nor replicas. 3 x 1,8" LCD TFT Panel

Display Type XGA 4/3 Liquid Crystal Display Ansi-Lumen

2100

Contrast 350:1 full on/off Black Level 6,0000 min. Lumen Offset

ω700 Lux (bei 200 cm Screen)
350:1 full on/off
2,017 min. Lumen

XGA 1024 x 768 Resolution

786.432 Pixel

SXGA 1280 x 1024 compressed

Video Modes PAL, PAL-M, PAL-N, PAL-60, SECAM, NTSC,

Stationary | Permanent installation in the training room and meeting room as well as the

A brief introduction to the Sanyo PLC 9000E/A/L. The LCD projector has an XGA 1024 x 768 resolution and a contrast of 350:1. The brightness of 2100 Ansi lumens enables a picture width

of 399 cm. In room light, the picture should be max. 266 cm wide. It was launched in 1999 and

is no longer offered by the manufacturer Sanyo. It should also be noted that, unfortunately, there

conference room.

Medium screen width or rooms with little light, max. 100 lumens.

400W Metalldampf Lamp Articel Nr.: 610 290 7698

Light Life 750 h.

**Operating Costs** 

Application

Light Source

Connections

**Focus** Powered

Zoom Powered 1,6

Objective optional

Throw Ratio optional

Audio 2 x 3W

> D-sub 15pin in 5 x BNC RGBHV in Cinch stereo in und out Cinch Video in

S-Video in **USB** 

Ceiling Mounting Yes Power

630W

389 x 213 x 582 mm (15,3"x8,4"x22,9") 48,22 L/dm3 Size WxHxD

**Operating Noise** 

368 - 588 cm Lux:700 Lux Room light max.:140 Lux Candela pro m<sup>2</sup>:223 cd/m<sup>2</sup> Foot-Lamberts:65 fL 4/3 screen width:200 cm Screen:1 Gain

Weight Keystone Illumination 85% H-sync: 15-80 kHz
V-sync: 50-100 Hz
Range max.: 135 MHz

Foot-Lamberts 65 fL / max. 399 cm screen width

223 cd/m<sup>2</sup>

■ Freeze

Features Remote control with mouse control

Overscan adjustable

Status 1999 Discontinued (EOL) // Last update of the data: 2023-08-04

Data







Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.