## Sharp PG D100E/U







**Brief Introduction** Beta 2.5

model, neither originals nor replicas. 3 x 1,3" LCD TFT Panel Display Type 32x 4/3 Liquid Crystal Display

Ansi-Lumen Contrast

Application

Light Source

Projector 4,00 100:1 full on/off Black Level 4,0000 min. Lumen

Offset

832 x 624 Pixel Resolution Video Modes

PAL/SECAM/NTSC 3.58/NTSC 4.43

Stationary | Permanent installation in the training room and meeting room as well as the

The Sharp PG D100E/U LCD projector has 400 Ansi lumens, a contrast of 100:1 and a

resolution. 400 Ansi lumens ensure that a picture width of 174 cm is also possible. However, if

room light is available, the picture should be a maximum of 116 cm wide. It is no longer offered

თ 129 Lux (bei 203 cm Screen)

100:1 full on/off 1.33 min. Lumen

by the manufacturer Sharp. Unfortunately, we can no longer offer replacement lamps for this

conference room.

Very narrow picture width and rooms with very little light.

265W Metalldampf Lamp Articel Nr.: PG-D100

2000 h. Light Life

**Operating Costs** 

Manual **Focus** 

Zoom Manual 1,4

Objective F=2,8-3,3 f=53-74 mm

Throw Ratio 1,48-2,07:1

Audio 2 x 3W

> D-sub 15pin in Mini Jack in RS232C Din 9 Port

Maus Port

Ceiling Mounting

Connections

Power 355W

Size WxHxD 264 x 119 x 389 mm (10,4"x4,7"x15,3") 12,22 L/dm<sup>3</sup>

**Operating Noise** 


7,50 kg / 16,53 lbs. Weight

Keystone Illumination

Frequenz

12 fL / max. 174 cm screen width Foot-Lamberts

41 cd/m<sup>2</sup>



Features

Status Data ■ Remote control with laser pointer und mouse control

- Discontinued (EOL) // Last update of the data: 2023-08-04

More Details





Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.