

Unis Unispro DX1

UNIS UNISPRO DX1



Brief Introduction

Beta 2.5

With the Unispro DX1, manufacturer Unis offers a DLP projector with XGA 1024 x 768 resolution and a contrast of 1000:1. An image width of up to 461 cm is possible. However, the picture should be smaller in room light. We recommend max. 307 cm. It is no longer offered by the manufacturer Unis.



1 x DLP Chip
XGA 4/3 Ti Digital Light Processing Chip

Display Type

Ansi-Lumen

2800

906 Lux (bei 203 cm Screen)

Contrast

1000:1 full on/off

1000:1 full on/off

Black Level

2,8000 min. Lumen

0.909 min. Lumen

Offset

-

Resolution

XGA 1024 x 768

786.432 Pixel

SXGA 1280 x 1024 compressed

Video Modes

PAL, SECAM, NTSC

Application

Standard-Portabel | External training and company presentations, as well as product presentations.

Light Source

200W Lamp

Light Life

-

Operating Costs

-

Focus

Manual

Zoom

Manual

Objective

-

Throw Ratio

-

Audio

1 x 3W

Connections

Cinch Stereo in

S-Video in

Mini Jack

USB

Ceiling Mounting

Yes

Power

290W

Size WxHxD

285 x 86 x 220 mm (11,2"x3,4"x8,7") 5,39 L/dm³

Operating Noise

-



Weight

3,00 kg / 6,61 lbs.

Keystone

-

Illumination

90%

Frequenz

H-sync: 30-90 kHz

V-sync: 56-85 Hz

Foot-Lamberts

84 fL / max. 461 cm screen width

288 cd/m²

Features

-

Status

- Discontinued (EOL) // Last update of the data: 2023-08-04

Data

More Details



HCinema

<https://www.projector-database.com/pro/unisUnisprodx1-en.html>

