



V7 PD 753

Product information

- Single 0.7" DLP™ Panel (Digital Light-Processing)
- Brightness: 1.600 ANSI Lumens High Brightness
- Noise Level typ.: 32 dB
- Lightweight Flat Design (2.9 kg)
- True XGA, 1024 x 768 Addressable Pixels
- 1.2 Zoom lens
- Remote Control with Mouse & Laser pointer
- NTSC/PAL/SECAM/HDTV Compatible with 4:3 & 16:9 Format
- SXGA Compression & 120 Hz High Refresh Compatible
- Auto Adjustment & High Quality Full Screen Re-scaling Image
- Multilingual On Screen Display Menu Adjustments
- Multimedia Audio Integration
- 760 TV Lines

Optical Features

- Contrast Ratio: 600:1 (on/off)
- Uniformity: 90 %
- Displayable Colours: 16.7 million colours
- Colour Temperature: 7500°k (6000°k – 9000°k)
- Lamp Type: 200 Watt user replaceable UHP lamp
- Lamp Life: 2.000 hours max.
- Projection Lens: $F = 2.44 \sim 2.69$, $f = 28.8 \sim 34.5$
- Zoom Factor: 1.2X, Manual
- Projection Screen Size: 0.56 m - 7,75 m
- Projection Distance: 1.14 m - 12.4 m
- Throw Ratio (Projection Distance / Image Width): 2.0 ~ 2.5

Electrical Features

- Horizontal Scan Rate: 15 ~ 100 kHz
- Vertical Refresh Rate: 43 ~ 120 Hz
- Pixel Frequency 160 MHz
- Aspect Ratio: 4:3, support 5:4/16:9 (wide screen compatible)
- Video Compatibility: NTSC (M, 4.43, und 3.58)
- PAL (B, D, G, H, I, M, N)
- SECAM (B, D, G, K, K1, L)
- HDTV (1080i, 720p) supports 480p/i and 576p/i

Mechanical Features

- Unit Dimension (HxWxD): 277 x 225 x 85 mm
- Source: VGA, DVI digital, DVI analog, S-Video, Composite, Component and HDTV
- Volume + / Volume - / Mute
- LED Control: Lamp (green colour), Temp (orange colour), Power/Standby (red colour)

- PC I/O Connectors:

Input: 1 x HD 15-Pin D-Sub (Component Video/HDTV input port)
1 x DVI Connector
1 x Audio Mini Jack (for 15 pin D-Sub)
1 x Audio Mini Jack for DVI
Output: 1 x Mini D-Sub 15-pin for monitor Loop through

- Video I/O:

Input: 1 x Mini DIN for S-Video Input Connector
1 x RCA Jack for Composite Video Input Connector
1 x Phono Jack (Audio Input)
1 x RS 232 for Service
Output: 1 x Mini DIN Audio Output for VGA/Video

- Remote Mouse I/O - 1 x Remote Mouse port
- Keystone Correction: ± 16 degrees (32 degree)
- Multimedia Audio: 2 internal speakers with 3 Watts output

Accessories

- Lens Cover, AC Power Code, 2 AA Type Batteries, Soft Handle Carry Bag
 - Wireless Remote Control with mouse function and laser pointer
 - Video and Data Signal Cable: 1 x 15-pin VGA Signal Cable (1.8 m)
- 1 x S-Video Signal Cable
1 x Composite Video Cable (RCA to RCA)
1 x DVI to VGA Cable D-sub
- Audio Cable: 1 x Mini Phone Jack to two RCA Audio Cable
 - Y Cable for Remote Mouse cable (support USB/Com Port)
 - User Manual (CD and Quick Start Card) and Warranty Card
 - Optional: Ceiling Mount Kit with 5m wire, RS-232 Cable, 15 pin D-Sub to HDTV port (3-pin for HDTV function),
30 pin DVI-Signal DVI to DVI cable (1.8 m), Scart Adapter for UK

Warranty

- 3 years Pick-Up Service, 90 days on lamp