## Videoseven PL700 X









**Brief Introduction** 

Beta 2.5

The PL700 X LCD has 1300 Ansi lumens, a contrast of 400:1 and an XGA 1024 x 768 resolution. A built-in horizontal and vertical keystone correction provides freedom when positioning the projector. 314 cm image width, the projector will be able to illuminate well. However, if room light is available, the image width should ideally not exceed 209 cm. The model is no longer offered by Videoseven. Unfortunately, we can no longer offer replacement lamps for this model, neither originals nor replicas. 3 x 0,7" LCD TFT Panel

თ433 Lux (bei 200 cm Screen) შ 400:1 full on/off 1.091 min. Lumen

Display Type

XGA 4/3 Liquid Crystal Display

Ansi-Lumen Contrast

1300 400:1 full on/off 3,2500 min. Lumen

Black Level Offset

Resolution

XGA 1024 x 768 786.432 Pixel

SXGA 1280 x 1024 compressed

Video Modes

NTSC 4.43, PAL, PAL-M, SECAM

Standard-Portabel | External training and company presentations, as well as product

Application

presentations.

Small screen width, rooms with very little ambient light below 100 lumens.

Light Source

150W EHP Lamp Articel Nr.: PL 700X

Light Life

1500 h.

**Operating Costs** 

Manual

Zoom

Focus

Manual 1,3

Objective

Throw Ratio

Audio

2 x 1W

Connections

Cinch Video in S-Video in

Ceiling Mounting

Yes

Power Size WxHxD

Frequenz

210W

270 x 70 x 210 mm (10,6"x2,8"x8,3") 3,97 L/dm3

**Operating Noise** 

35dB

Weight 2,60 kg / 5,73 lbs. Vert.: +/-15° Keystone Hori .: +/-10°

Illumination 85%

> H-sync: 15-91 kHz V-sync: 50-85 Hz Range max.: 157 MHz

40 fL / max. 314 cm screen width Foot-Lamberts

Lux:433 Lux Room light max.:87 Lux Candela pro m2:137 cd/m2 Foot-Lamberts:40 fL 4/3 screen width:200 cm Screen:1 Gain

137 cd/m<sup>2</sup>

Freeze

■ Kensington Slot

■ Gamma correction

■ Picture-in-Picture

■ Remote control with laser pointer und mouse control

- Discontinued (EOL) // Last update of the data: 2023-08-04

Status

Features

Data

More Details





Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.