

LS810



1280 x 800 Resolution, 5,200 Lumens, 0.25 Throw Ratio




Key Features:

- Long-lasting laser phosphor light source
- 5,200 lumen brightness
- Large images in small spaces
- Ultra-high contrast ratio
- Secure MHL/HDMI port

Featuring 1280x800 WXGA resolution and 5,200 lumens of brightness, the ViewSonic® LS810 Laser Projector is the ideal solution for modern business and education environments. Designed with a laser phosphor light source lasting up to 20,000 hours, this projector delivers long-term, virtually maintenance-free usage for any boardroom or classroom. With its 0.25 ultra-short throw ratio, HV keystoneing and 4 corner adjustments, the LS810 makes installation a hassle-free experience. What's more, the ultra-short throw ratio allows you to place the projector just inches away from a wall or screen to give you a huge image for less cost than a comparably sized display. The LS810 also features a hidden PortAll® compartment which accommodates additional accessories such as a wireless streaming device, or PC stick. Powered by SuperColor™ technology for true-to-life images, and SonicExpert® technology for incredibly clear sound, the LS810 delivers an immersive audiovisual performance.

Dimensions:



Full Specifications

Display

Throw Distance:	1.21 – 2.62 ft. / 0.37 – 0.8 m
Throw Ratio:	0.25
Type:	DLP
Lens:	Digital optical focus

Operating Conditions

Temperature:	32-104° F (0–40° C)
Humidity (non-condensing):	0-90%

Weight (imperial)

Net (lbs):	22.05
------------	-------

Keystone:	Vertical (± 30°) / Horizontal (± 30°)
Light Source (watt):	390
Light Source Life, Normal (hours):	15000
Light Source Life, Dynamic Eco-Mode (hours):	20000
Brightness (ANSI Lumens):	5,200
Color Depth:	30 bits, 1.07B Color (10+10+10)
Resolution:	1280 x 800
Dynamic Contrast Ratio:	100000:1
Aspect Ratio:	16:10
Resolution Type:	WXGA
Display Size (in.):	70 – 150 in. / 1.78 – 3.81 m (diagonal)

Video Signal

Frequency Horizontal:	15–100KHz
Frequency Vertical:	24–120Hz

Compatibility

PC Resolution (max):	Up to 1920x1080
Mac® Resolution (max):	Up to 1920x1080 (may require MAC adapter)

Connector

USB 2.0 Type A(1), Ethernet LAN (RJ45)(1), 3.5mm Audio Out(1), 3.5mm Audio In(1), HDMI 1.4(1), HDMI MHL(1), VGA In(2), VGA Out(1), Composite RCA Video In(1), Component RCA(1), S-Video In(1), Mini USB(1), Micro USB(1)

Audio

Internal Speakers:	8W (x2)
--------------------	---------

Power

Voltage:	AC 100-240V (universal), 50-60Hz
Consumption (max):	450W
Stand-by:	<0.5W

Controls

Physical Controls:	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
On Screen Display:	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)

Gross (lbs):	33.07
--------------	-------

Weight (metric)

Net (kg):	10.0
Gross (kg):	15

Dimensions (metric) (WxHxD)

Packaging (mm):	550 x 570 x 310
Physical (mm):	508 x 392 x 165

Dimensions (imperial) (WxHxD)

Packaging (in.):	21.65 x 22.44 x 12.2
Physical (in.):	20.0 x 15.4 x 6.5

General

Regulations: Mexico Energy test/Registration, EAC, TUV-S Mark (Argentina), India BIS, FCC, CE, EMC, CB, CCC, RoHS, REACH, SVHC, WEEE, ErP, Mexico NOM, cTUVus, PSB, RCM, CECF

PACKAGE CONTENTS: LS810 projector, power cable, VGA cable, HDMI Cable, remote control with batteries, Quick Start Guide, ViewSonic Wizard CD (with User Guide)

Warranty: Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service**

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

UPC: 766907847413

Accessories

BCP100, BCP120, HB10B, PGD-350, PJ-WMK-006, VIEWSTICK2, VIEWSYNC3, WPG-300