

PJ400

LIGHT, BRIGHT AND PORTABLE PROJECTOR

WITH KEYSTONE CORRECTION

Portable and multifunctional.

The ViewSonic® PJ400 weighs only 4.9 pounds but packs big power into its compact package. With native SVGA 800x600 resolution and 1,600 lumens, the PJ400 is BRIGHT AND POWERFUL ENOUGH FOR VIRTUALLY ANY SITUATION. Advanced video features such as progressive scan and 3:2 pull down deliver smooth, crisp video performance. Project sharp, precise images from your data applications as well. DELIVER DYNAMIC MULTIMEDIA PRESENTATIONS with multiple inputs and HDTV signal support. This full-featured projector is an excellent choice for professional presentations or home entertainment use.



DELIVER BRILLIANT PRESENTATIONS

- > **Bright in virtually any setting with 1,600 lumens**
Packs 1,600 lumens in just 4.9 lbs. It's the bright choice for mobile presenters.
- > **Ultimate video source flexibility**
Connect a computer or add a video source for dynamic meetings and presentations.
- > **Supports HD signals including 720p and 1080i**
Capable of displaying HDTV signals as well as other video and data sources*
- > **Advanced video features**
Progressive scan and 3:2 pull down for superior video performance.
- > **Whisper-mode extends lamp life**
Extend the life of your lamp up to 4,000 hours** and reduce noise output.
- > **OnView® controls plus ViewMatch® color for superior screen adjustability**
Screen geometry and color adjustments are precisely made via an easy-to-use, on-screen menu.
- > **The best warranty in the business**
Covered by a three-year parts and labor limited warranty, first-year Express Exchange® and one-year limited lamp warranty.***



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

PJ400

LIGHT, BRIGHT AND PORTABLE PROJECTOR WITH KEYSTONE CORRECTION



Optional Accessories

- Replacement lampRLC-004
- Hard case with wheelsPRJ-HCA-001
- Extended Express Exchange®PRJ-EE-05-03
- Soft case with wheels and laptop bagPRJ-SCA-004
- Universal ceiling mount kitWMK-005
- VGA to component video adapter ...ADPT-002

| | | |
|-------------------------------|-------------------------|--|
| PROJECTOR | Type | 0.55" Poly-Si TFT with micro-lens |
| | Pixel Format | 800x600 SVGA |
| | Lens | Digital zoom, manual focus |
| | Zoom Factor | 1.2 (digital) |
| | Keystone | Vertical ± 15° |
| DISPLAY | Size | 40"-300" (diagonally) |
| | Throw Distance | 60"-456" |
| | Throw Ratio | 1.9:1 |
| | Lamp | 165W, 2,000 hours** |
| | Brightness | 1,600 ANSI lumens |
| | Contrast Ratio | 300:1 |
| | Aspect Ratio | 4:3 (native), 16:9 |
| AUDIO | Speakers | 1x1 watts |
| INPUT SIGNAL | Video | RGB analog, NTSCM, NTSC 4.43, PAL, SECAM, HDTV (480i, 480p, 576i, 720p, 1080i) |
| | Frequency | F _H : 15-92kHz; F _V : 56-120Hz |
| COMPATIBILITY | PC | Analog: from VGA up to UXGA (scaled) |
| | Mac®† | Analog: up to SXGA (may require a Mac adapter) |
| CONNECTOR | RGB (input) | 15-pin HD, D-sub cable (x1) |
| | Composite Video (input) | RCA jack (x1) |
| | S-Video (input) | Mini-Din 4-pin (x1) |
| | Component Video (input) | VGA DB-15 to component adapter* |
| | Audio (input) | Stereo mini-jack (x1) |
| | Control | 9-Pin D-sub for RS232 control |
| POWER | Voltage | 100-240 VAC, 50-60Hz (universal) |
| | Consumption | 240W (typ) |
| CONTROLS | Basic | Standby, input, reset, H/V keystone |
| | OnView® | Language, brightness, contrast, gamma, color temperature, color, tint, sharpness, progressive, My Memory, aspect, overscan, V. position, H. position, H. phase, H. size, auto adjust, color space, component, video format, information, V. keystone, whisper, mirror, volume, language, menu position, OSD bright, blank color, start up, My Screen, My Screen Lock, message, auto search, lamp time, filter time, service menu |
| OPERATING CONDITIONS | Temperature | 32-95°F (0-35°C) |
| | Humidity | 10-85% (non-condensing) |
| NOISE LEVEL | Normal | 38 dB (typ) |
| | Whisper Mode | 33 dB (typ) |
| DIMENSIONS (W x H x D) | Physical (mm) | 285mm x 73mm x 202mm |
| | Physical (in.) | 11.2" x 2.9" x 8.0" |
| WEIGHT | Net | 4.9 lb. (2.2 kg) |
| | Gross | 12.1 lb. (5.5 kg) |
| REGULATIONS | | UL 60950, C-UL, FCC-B, UL-DEMKO/GS, CCC, CB, CE, C-TICK, GOST, NOM, PSB, TUV-S |
| OTHER | | Vertical digital keystone correction, progressive scan, 3:2 pull down, auto adjust, remote control |
| WARRANTY | | Three-year limited warranty on parts and labor, first-year Express Exchange® Service. One-year limited warranty on lamp*** |

ViewSonic® 

the choice of professionals

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Optional cables required. **Running whisper-mode exclusively can extend lamp life. ***Visit ViewSonic.com for full details. †Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs vary by country. See your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2006 ViewSonic Corporation. All rights reserved. [12745-01B-03/06] PJ400-2

For more product information, visit us on the web at ViewSonic.com