Viewsonic PJ751







Brief Introduction

Beta 2.5

The standard portable PJ751 LCD projector from Viewsonic has 2500 Ansi lumens, a contrast of 400:1 and an XGA 1024 x 768 resolution. Thanks to the brightness of 2500 Ansi lumens, a picture width of 435 cm is possible. In room light, the picture should be max. 290 cm wide. This model is no longer offered by Viewsonic.

Display Type

X X

3 x 0,9" LCD TFT Panel XGA 4/3 Liquid Crystal Display

Ansi-Lumen Contrast Black Level

Offset

ਹੁੰ ਰੂੰ 400:1 full on/off ਰੂੰ 6,2500 min. Lumen XGA 1024 x 768 786.432 Pixel

786.432 Pixel SXGA 1280×1024 compressed

.

PAL-M, PAL-N, PAL-60, SECAM, NTSC, HDTV 720p, 1080i,

Video Modes

Resolution

Standard-Portabel | External training and company presentations, as well as product

Application

presentations.

Medium screen width or rooms with little light, max. 100 lumens.

200W Lamp

Light Source

Light Life

Focus

Articel Nr.: PRJ-RLC-001 2000 h. 4000 h. in Eco Mode

Operating Costs

Zoom -

Objective -

Throw Ratio -

Audio -

2 x D-sub 15pin in

1 x YUV in

1 x Cinch Video in 1 x Cinch Stereo in

1 x S-Video in

1 x USB in 1 x RS232C in

Mini Jack in

Ceiling Mounting

Connections

Power 290

290W / 160W in Eco Mode


Size WxHxD 298 x 76 x 228 mm (11,7"x3"x9") 5,16 L/dm³

Operating Noise -

Weight

Keystone Vert.: +/-10°

Illumination



Frequenz H-sync: 15-91 kHz V-sync: 56-120 Hz

Foot-Lamberts 75 fL / max. 435 cm screen width

257 cd/m²

Freeze

■ Blank (Black screen button)

■ User logo

Gamma correction

■ Remote control with laser pointer und mouse control

Overscan adjustable

Bulb only NLMP4240

Lamp ruby Ruby-LMP4240

Optional Lamp original PRJ-RLC-001

Universal Remote original Fernb-uni-V3

Order here: https://www.hcinema.de/lampen/shop-en.php?id=n17707

atus 2004 Discontinued (EOL) // Last update of the data: 2023-08-04

Status 2004 Discontinued (EOL) // Last u Data

More Details





Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.