Viewsonic PJD6210 3D







Display Type

1 x 0,55" DLP Chip

XGA 4/3 Ti Digital Light Processing Chip

Ansi-Lumen

2000:1 full on/off

Contrast Black Level

0,8100 min. Lumen

Offset

XGA 1024 x 768

Resolution

786.432 Pixel SXGA 1280 x 1024 compressed

Video Modes

PAL, SECAM, NTSC, HDTV 720p, 1080i, EDTV 480p, 576p

3D Compatibility

Frame Sequential (3D Ready)

Application

Standard-Portabel | External training and company presentations, as well as product presentations.

ωLux (bei 200 cm Screen)

394 - 432 cm

2000:1 full on/off

Very narrow picture width and rooms with very little light.

Light Source

Light Life

Operating Costs

Focus Manual

Manual 1,1

1,97-2,16:1

Objective

Throw Ratio

Connections

Zoom

Audio

D-sub 15 pin in

S-Video in

Cinch Video in

RS232C

Ceiling Mounting Yes Power 240W

Size WxHxD 273 x 108 x 215 mm (10,7"x4,3"x8,5") 6,34 L/dm3

Operating Noise 34 / 32 dB in Eco Mode

Key: 331 cm

4/3 screen width:200 cm

Screen:1 Gain

2,40 kg / 5,29 lbs. Weight Keystone Vert.: +/-40°

Illumination



Frequenz H-sync: 31-79 kHz V-sync: 50-85 Hz

Foot-Lamberts -

■ Eco Mode

Features Gamma correction
Password protection

■ BrilliantColor™

Status 2008 Discontinued (EOL) // Last update of the data: 2023-08-04

Data











More Details





Key: 331 cm

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.