## **Vivibright PDS500**







**Brief Introduction** 

The standard portable PDS500 DLP projector from Vivibright has 2600 Ansi lumens, a contrast of 2500:1 and an SVGA 800 x 600 resolution. The lamp life is specified by the manufacturer as 4000 hours, which is over 5.5 years with a daily viewing time of 2 hours. A picture width of up to 444 cm is possible. However, the picture should be smaller in room light. We recommend max. 296 cm. The model was built by Vivibright in 2011 and is no longer current.

Display Type

1 x 0,55" DLP Chip

SVGA 4/3 Ti Digital Light Processing Chip

Ansi-Lumen Contrast Black Level

2600 / 2200 im Eco Mode 2500:1 full on/off 1,0400 min. Lumen

0,347 min. Lumen

Resolution

Video Modes

Application

Offset

SVGA 800 x 600 480.000 Pixel

UXGA 1600 x 1200 compressed

PAL, SECAM, NTSC, HDTV 720p, 1080i, EDTV 480p, 576p

Standard-Portabel | External training and company presentations, as well as product

presentations.

Medium screen width or rooms with little light, max. 100 lumens.

Light Source 180W UHO Lamp

Light Life 4000 h. 5000 h. in Eco Mode

**Operating Costs** 

**Focus** Manual

Zoom Manual 1,1

Objective F=2,41-2,55 f=21,8-23,98 mm

Throw Ratio 1,95-2,15:1

Audio

2 x D-sub 15 pin in 1 x out

YUV in Connections S-Video in USB in

Ceiling Mounting Yes 220W

Size WxHxD 445 x 135 x 330 mm (17,5"x5,3"x13") 19,82 L/dm3

**Operating Noise** 31dB

Weight 2,20 kg / 4,85 lbs. Keystone Vert.: +/-30° Illumination 95%

H-sync: 15-150 kHz Frequenz V-sync: 48-190 Hz

Foot-Lamberts 81 fL / max. 444 cm screen width


> 278 cd/m<sup>2</sup> Eco Mode


2011 Discontinued (EOL) // Last update of the data: 2023-08-04

Status Data

**Features** 

Power





## More Details



Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.