

HOME THEATER PROJECTOR

H9030FD

Take Home Entertainment to an Extreme Level with LED

LED extreme short-throw delivered by Vivitek with the H9030FD home theater projector.

Create an 88-inch image from about 15-inch away with stunning images. As an LED-based projector, the H9030FD is unmatched by traditional lamp-based projectors. With its assortment of connectivity options and a built-in speaker, the H9030FD is the ultimate home entertainment solution for tight spaces.

Features

- High Contrast at 50,000:1
- LED light source provides ≈20,000 hours of operation
- Full HD 1080p (1920x1080)
- 3D-Ready
- 88-inch image from about 15-inches away
- Connectivity options include: Three (3) HDMI v1.3, VGA-In, S-Video, Composite Video, Component Video













Native Resolution 108 Max. Resolution UX	00 ANSI Lumens 30p (1920 x 1080) GA (1600 x 1200)
Max. Resolution UX	
	GA (1600 x 1200)
Contrast Ratio 50,	, ,
1	000:1
Lamp Life and Type ≈20	0,000 Hours, LED
	gle 0.65" DLP® DarkChip2™ Technology by cas Instruments
Throw Ratio 0.1	8:1 (Distance/Width)
Image Size (Diagonal) 88.	5"
Projection Distance 15'	1
Projection Lens Mc	anual Focus
Aspect Ratio Na	tive 16:9, 4:3 Compatible
Keystone Correction ±15	5° Vertical
Color Spectrum 1.0	7 Billion
Horizontal Scan Rate 15,	30 to 90kHz
Vertical Scan Rate 43	to 85 Hz
Speaker TBE	
Remote Control IR F	Remote
Projection Method Tak	ole Top or Ceiling (Front or Rear)
Uniformity 859	%
Compatibility VG	30p, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, GA, Resized; VESA Standards; PC and Macintosh impatible
1 1	TV(480i), EDTV (480p), HDTV (720p, 1080i/p), SC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM
Vic	MI v1.3 (x3), VGA-In, S-Video, Composite deo, Component Video, RCA Stereo Audio-In, ni-Jack Audio In, RS-232c, 12v Trigger
Security Kes	sington® Lock Port
Weight TBD	
Dimensions (W x H x D) TBE	
Noise Level 28	dB
	oply: AC 100-240V, 50/60Hz onsumption: TBD, <1W (Standby Mode)
Operating Temperature 41	to 104°F (5 to 40°C)
Warranty 1 Y	ear Limited Parts and Labor, 90-Day Lamp
	Power Cord, VGA Cable, Remote Control, tteries for Remote, User's Manual, Warranty ard
Optional Accessories Re	placement Remote Control
UPC TBE	